

LT-Light Traffic COMMERCIAL SYSTEM



For all your temporary surface protection needs, Skudo's got you covered

Description

Skudo's LT Commercial System is designed to protect interior surfaces from light construction traffic for up to 6 months. It is comprised of a flexible, peelable Concrete Base Coat and the LT (Light Traffic) Mat.

The LT Mat gently adheres to the surface it's protecting, creating a homogeneous barrier that does not permit debris to get underneath.

The system also provides a safe working environment with a seamless and slip resistant surface that will not move, lip or curl. Once the project is completed, the Mat is simply peeled up and disposed of in general site refuse facilities.



Uses

- Countertops & Cabinetry
- Tubs & Showers
- Staircases, Walls & Doors
- Interior Use - up to 6 months
- Exterior Use - NEVER

Benefits

- ✓ Reliable surface protection for Light Traffic on site
 - Protects against foot traffic, carts, wheelbarrows, trolleys, scaffolding
 - Dirt and debris stay on top of Skudo without touching the protected surface
 - Light spill, stain and water resistance
 - Resistance to mold
- ✓ Safer working surface
 - High slip resistance
 - Seamless and stationary
- ✓ Minimal maintenance - Won't slide, curl or become soggy
- ✓ Cleans surface upon peel up removal



Application

The Skudo LT Commercial System is applied in two layers:

- (1) The water based Concrete Base Coat is applied using either our Squeegee Method (preferred) or Roller Method. See application sheet for details.
- (2) The LT Mat is rolled out and pressed into the wet Base Coat. For more information on correct application methods, please refer to our Website, Product Application Sheet or Label.



Substrate Suitability

Raw Concrete (Smooth)	Not Suitable	Tiles - Porcelain	Excellent
Polished Concrete (Sealed)	Not Suitable	Marble / Stone - Smooth	Excellent
Decorative Concrete	Not Suitable	Marble / Stone - Coarse	Good
Brushed Concrete	Not Suitable	Epoxy Coated Surfaces	Very Good
Aged Concrete	Not Suitable	Primed Steel	Excellent
Stairs	Good	Fiberglass	Excellent
Hardwood (Sealed)	Excellent	Laminate	Excellent
Tiles - Ceramic	Excellent	High Pressure Laminate	Excellent

Product Coverage

LT Mat	1075 sq. ft./roll
Base Coat	
Troweled/Textured Surfaces	130 sq. ft./gal
Smooth Surfaces	150 sq. ft./gal

The surfaces listed above provide a guide only and vary due to a range of factors. For substrates not listed above, please refer to your Skudo representative. All substrates should be tested for suitability by doing a small spot test. No warranties implied or otherwise are given for the usage of this product