



## Description

Skudo CURE™ is a penetrating curing agent that chemically hardens and dust-protects concrete for improved abrasion resistance without forming a coating on the surface.

Skudo CURE™ is recommended on newly placed concrete to retain moisture in the slab for improved curing characteristics while increasing the initial water and stain repellency of the surface. It can be used with integrally colored concrete.

Skudo CURE™ was designed for use on decorative concrete; it requires no UV light for dissipation and will not stop the penetration of densifiers or dyes into the surface.

The penetrating nature of the Skudo CURE™ means that the aggressive abrasives or strippers that are required for some traditional topical curing products are no longer required - saving time when prepping the surface.



## Features

- Improves cure by retaining slab moisture
- Drastically reduces crazing and map cracking
- High penetrating, non-film forming – no need to grind or chemically remove layer to seal and burnish
- Forms hydrophobic barrier and increases stain repellency
- Greatly improves abrasion resistance
- Helps reduce efflorescence and minimizes dusting of the concrete
- Replaces traditional Cure & Seal products on new concrete
- Coverage rate is approximately 1,000-1,500 ft<sup>2</sup> per GALLON

\*Compared to standard topical coverage rates of 200 - 400 ft<sup>2</sup> per GALLON

## Product Details

### PRODUCT SPECIFICATIONS

<b>Application</b>	Spray and microfiber pad
<b>Appearance</b>	Milky liquid
<b>VOC</b>	Compliant (1g/l)
<b>Shelf Life</b>	1 year
<b>Solvent</b>	Water Based

**Innovative, purpose-built surface protection systems. This is all we do.**

[www.skudousa.com](http://www.skudousa.com) 1-888-SKUDO-11 (1-888-758-3611)



**PACKAGING SPECIFICATIONS**

Product SKU	Shipping Weight	Container(s) RTU (Ready to Use)
CT-CURE-5GAL	50 lbs	RTU - 5 Gallons
CT-CURE-55GAL	550 lbs	RTU - 55 Gallons

**COVERAGE**

Product SKU	Volume (RTU)	Coverage - Sq. Ft/Unit
CT-CURE-5GAL	5 Gal.	5,000 - 7,500
CT-CURE-55GAL	55 Gal.	55,000 - 82,500

**Warranty**

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.

NOTE: Over burnishing of the concrete with trowels will impede the penetration of the Skudo CURE™ into the concrete surface.

**Caution**

Before using or handling this material, read the Material Safety Data Sheet and Warranty. EYE, SKIN AND GASTRO-INTESTINAL TRACT AND RESPIRATORY TRACT IRRITANT. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists generated by this product. Use appropriate eye protection, and chemical-resistant gloves. Material is not flammable, but if exposed to fire material may produce irritating vapors and toxic gases (e.g., carbon dioxides and peroxides). KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.



**DEGREE OF HAZARD**

- 4=EXTREME
- 3=HIGH
- 2=MODERATE
- 1=SLIGHT
- 0=INSIGNIFICANT



**Innovative, purpose-built surface protection systems. This is all we do.**

[www.skudousa.com](http://www.skudousa.com) 1-888-SKUDO-11 (1-888-758-3611)