







# **Description**

Skudo Edge Protect Tack-Mat has been specifically designed and sized to protect window frames, ledges, railing, door jambs, and other indoor framing and edges during construction. With both 8 inch and 12 inch width rolls available, there is no longer a need to cut down rolls which helps to save time, labor, and waste. Also, like all Skudo Tack-Mat products, Edge Protect features a unique self-stick surface - simply peel the backing paper and apply.

Skudo Edge Protect provides interior surface protection for commercial and residential projects for up to 12 months.



Perfect for framing

Peel up and re-apply



# Protect edges from damage

EDGE PROTECT

Durable

## **Benefits**

- Strong bond with the surface blocks any dirt and debris from ever coming into contact with the protected substrate
- Impact protection from carts, ladders, tools, and more
- Stain proof protection from small spills of chemicals, solvents, paints, oils etc.
- Seamless and stationary won't move out of place
- Can be used in any temperature: -20°F to +200°F
- Easy to adjust or inspect surface, simply peel up and reposition

## **Uses**

Protects all edges during construction / remodeling including:

- Glass & Metal framing, ledges, and railing
- Ceramic and Porcelain Tile
- Marble, Granite, and Stone\*
- Vinyl, Laminate, and Hardwood\*

<sup>\*</sup>Please see "Limitations" section (pg 2)





#### **Application & Removal**

All Skudo Tack-Mat products are easily applied by peeling off the release paper and pressing down onto the surface. Simply peel up Tack-Mat leaving a clean, undamaged surface.



For detailed step-by-step Tack-Mat application directions and video, please visit our website: https://www.skudousa.com/products/tack-mat/#how-to-apply



Easy Application

### **Edge Protect Tack-Mat Product Data**

Dimensions: 12"W x 82'L
Coverage: 82 sq. ft./roll
Product #TM-EP-12i-82

Color: Grey

Weight: 8.5 lbs./rollThickness: 1/16"

#### Limitations

- INTERIOR USE ONLY. Skudo Tack-Mat is intended for interior use only and is not suited for areas that will be exposed to inclement weather and wind. If exposure to the elements is a concern, please consult with your Skudo representative to discuss the best protection options for your project.
- All adhesives have the potential to lift finished coatings or paint depending on the condition and age of the surface.
   Testing a small piece in a non-critical area will help you judge suitability for use.
- If applying to hardwood flooring, only use Skudo Tack-Mat on sealed hardwood with a hard wearing factory finished surface (eg: Aluminum Oxide). If in question, please contact Skudo for suitability testing.

- If applying vertically, space must be conditioned. Humidity can cause this system to release from the substrate.
- Skudo Tack-Mat should NOT be applied to:
  - Concrete
  - Limestone
  - Rough/Textured Surfaces
  - Non-factory finished Hardwood
  - Raw or unfinished Timber/Hardwood
  - Any exterior surfaces

Please consult with your Skudo representative to determine which Skudo product is best for your project.