



EDGE
PROTECT



Learn More!



Description

Skudo Edge Protect Tack-Mat has been specifically designed and sized to protect window frames, ledges, railing, door jambs, and other indoor framing and edges during construction. With both 8 inch and 12 inch width rolls available, there is no longer a need to cut down rolls which helps to save time, labor, and waste. Also, like all Skudo Tack-Mat products, Edge Protect features a unique self-stick surface - simply peel the backing paper and apply.

Skudo Edge Protect provides interior surface protection for commercial and residential projects for up to 12 months.

Benefits

- Strong bond with the surface blocks any dirt and debris from ever coming into contact with the protected substrate
- Impact protection from carts, ladders, tools, and more
- Stain proof protection from small spills of chemicals, solvents, paints, oils etc.
- Seamless and stationary - won't move out of place
- Can be used in any temperature : -20°F to +200°F
- Easy to adjust or inspect surface, simply peel up and re-position

Uses

Protects all edges during construction / remodeling including:

- Glass & Metal framing, ledges, and railing
- Ceramic and Porcelain Tile
- Marble, Granite, and Stone*
- Vinyl, Laminate, and Hardwood*

*Please see "Limitations" section (pg 2)



Perfect for framing



Peel up and re-apply



Protect edges from damage



Durable



Innovative, purpose-built surface protection systems. This is all we do.

www.skudousa.com 1-888-SKUDO-11 (1-888-758-3611)

V 2.5 4.18.23



EDGE
PROTECT



Application & Removal

All Skudo Tack-Mat products are easily applied by peeling off the release paper and pressing down onto the surface. Simply peel up Tack-Mat leaving a clean, undamaged surface.



For detailed step-by-step Tack-Mat application directions and video, please visit our website:
<https://www.skudousa.com/products/tack-mat/#how-to-apply>



Easy Application

Edge Protect Tack-Mat Available Sizes & Product Data

- | | | |
|---------------------------------|---------------------------------|----------------------------------|
| • Dimensions: 8"W x 50'L | • Dimensions: 8"W x 82'L | • Dimensions: 12"W x 82'L |
| • Coverage: 33.3 sq. ft./roll | • Coverage: 61.5 sq. ft./roll | • Coverage: 82 sq. ft./roll |
| • Product #TM-EP-8i-50 | • Product #TM-EP-8i-82 | • Product #TM-EP-12i-82 |
| • Color: Grey | • Color: Grey | • Color: Grey |
| • Weight: 3.5 lbs./roll | • Weight: 6.4 lbs./roll | • Weight: 8.5 lbs./roll |
| • Thickness: 1/16" | • Thickness: 1/16" | • Thickness: 1/16" |

Limitations

- **INTERIOR USE ONLY.** Skudo Tack-Mat is intended for **interior use only** and is not suited for areas that will be exposed to inclement weather and wind. If exposure to the elements is a concern, please consult with your Skudo representative to discuss the best protection options for your project.
- **All adhesives have the potential to lift finished coatings or paint depending on the condition and age of the surface.** Testing a small piece in a non-critical area will help you judge suitability for use.
- If applying to hardwood flooring, only use Skudo Tack-Mat on sealed hardwood with a hard wearing factory finished surface (eg : Aluminum Oxide). If in question, please contact Skudo for suitability testing.
- If applying vertically, **space must be conditioned.** Humidity can cause this system to release from the substrate.
- **Skudo Tack-Mat should NOT be applied to:**
 - Concrete
 - Limestone
 - Rough/Textured Surfaces
 - Non-factory finished Hardwood
 - Raw or unfinished Timber/Hardwood
 - Any exterior surfaces

Please consult with your Skudo representative to determine which Skudo product is best for your project.

Innovative, purpose-built surface protection systems. This is all we do.

www.skudousa.com 1-888-SKUDO-11 (1-888-758-3611)

V 2.5 4.18.23