







Extreme Protection - High Impact

The HIGH IMPACT (HI) version of the Skudo Tack-Mat offers superior impact resistance in addition to the usual temporary surface protection expected from Skudo's products. Like all Skudo Tack-Mat products, the HIGH IMPACT product features a unique repositionable self-stick backing - simply peel the backing paper and apply. The HIGH IMPACT Tack-Mat can be used on both horizontal and vertical interior surfaces, around corners such as stairs and door jambs, on countertops, cabinets, windows and more.

HIGH IMPACT Tack-Mat provides interior surface protection for commercial and residential projects for up to 12 months.



- Superior impact resistance for delicate surfaces
- Strong bond blocks dirt and debris from contact with the protected surface
- Stain resistant protection against chemicals, solvents, paints, oils and other liquids
- Provides a durable, slip resistant stationary surface
- Can be used in any temperature: -20°F to +200°F
- Easy to adjust or inspect surface, simply peel up and reposition

Uses

Protects all surfaces during construction / remodeling including:

- Marble, Granite, & Stone*
- Hardwood* and laminate
- Ceramic and Porcelain Tile
- Glass, Epoxies, and Metals
- Sheet Vinyl
- Vertical surfaces, such as walls, cabinets, doors, framing, and stairs
- Showers, bathtubs, and countertops

*Please see "Limitations" section (pg 2)



Superior Impact Protection



Versatile usage



Protects many surface types



Perfect for high traffic zones





Application & Removal

All Skudo Tack-Mat products are easily applied by peeling off the release paper and pressing down onto the surface. Simply peel up Tack-Mat leaving a clean, undamaged surface.



For detailed step-by-step Tack-Mat application directions and video, please visit our website: https://www.skudousa.com/products/tack-mat/#how-to-apply



Easy Application

High Impact (HI) Tack-Mat Product Data

Width : 40"Roll Weight : 42 lbsLength : 65'Color : Grey

Surface Area : 215 SF
Product SKU : TM-HI-3.3-65-IMPACT

Mat Thickness : 1/6"

Limitations

- INTERIOR USE ONLY. Skudo HI Tack-Mat is intended for interior use only and is not suited for areas that will be exposed to inclement weather and wind. If exposure to the elements is a concern, Skudo recommends the Heavy Traffic (HT) Commercial Mat System. Please consult with your Skudo representative for more details.
- All adhesives have the potential to lift finished coatings or paint depending on the condition and age of the surface.
 Testing a small piece in a non-critical area will help you judge suitability for use.
- If applying to hardwood flooring, only use Skudo Tack-Mat on sealed hardwood with a hard wearing factory finished surface (eg: Aluminum Oxide). If in question, please contact Skudo for suitability testing.

- If applying vertically, space must be conditioned. Humidity can cause this system to release from the substrate.
- Skudo Tack-Mat should NOT be applied to:
 - Concrete
 - Limestone
 - Rough/Textured Surfaces
 - Non-factory finished Hardwood
 - Raw or unfinished Timber/Hardwood
 - Any exterior surfaces

Please consult with your Skudo representative to determine which Skudo product is best for your project.

Innovative, purpose-built surface protection systems. This is all we do.