





Description

Skudo's Light Traffic (LT) Construction Tack-Mat offers outstanding temporary surface protection that is easy to apply to both vertical and horizontal indoor surfaces, around corners such as stairs and door jambs, on countertops, cabinets, windows and more. LT Tack-Mat features a unique self-stick surface - simply peel the backing paper and apply.

LT Tack-Mat provides interior surface protection for commercial and residential projects for up to 12 months.

Benefits

- Strong bond with the surface blocks any dirt and debris from ever coming into contact with the protected substrate
- Impact protection from carts and foot traffic
- Stain proof protection from small spills of chemicals, solvents, paints, oils etc.
- Provides a slip resistant surface that is seamless and stationary
- Can be used in any temperature : -20°F to +200°F
- Easy to adjust or inspect surface, simply peel up and reposition

Uses

Protects all surfaces during construction / remodeling including:

- Marble, Granite, & Stone*
- Hardwood* and laminate
- Ceramic and Porcelain Tile
- Glass, Epoxies, and Metals
- Sheet Vinyl
- Vertical surfaces, such as walls, cabinets, doors, framing, and stairs
- Showers, bathtubs, and countertops

*Please see "Limitations" section (flip side)




For Any Project Size







Protects from materials & dirt



Durable

Innovative, purpose-built surface protection systems. This is all we do. www.skudousa.com 1-888-SKUDO-11 (1-888-758-3611)



Application & Removal

All Skudo Tack-Mat products are easily applied by peeling off the release paper and pressing down onto the surface. Simply peel up Tack-Mat leaving a clean, undamaged surface.



For detailed step-by-step Tack-Mat application directions and video, please visit our website: https://www.skudousa.com/products/tackmat/#how-to-apply

Light Traffic (LT) Tack-Mat Product Data

: 40"

: 165'

- Width
- Lenath
- Surface Area
- : 550 SF • Mat Thickness : 1/16"
- Roll Weight
- Color
- Product SKU





Easy Application

- : 50 lbs
- : Grey
- : TM-I T-3.3-165

Limitations

- INTERIOR USE ONLY. Skudo LT Tack-Mat is intended for interior use only and is not suited for areas that will be exposed to inclement weather and wind. If exposure to the elements is a concern, Skudo recommends the Heavy Traffic (HT) Commercial Mat System. Please consult with your Skudo representative for more details.
- All adhesives have the potential to lift finished coatings or paint depending on the condition and age of the surface. Testing a small piece in a non-critical area will help you judge suitability for use.
- If applying to hardwood flooring, only use Skudo Tack-Mat on sealed hardwood with a hard wearing factory finished surface (eg: Aluminum Oxide). If in question, please contact Skudo for suitability testing.

- If applying vertically, space must be conditioned. Humidity can cause this system to release from the substrate.
- Skudo Tack-Mat should NOT be applied to:
 - Concrete
 - Limestone
 - Rough/Textured Surfaces
 - Non-factory finished Hardwood
 - Raw or unfinished Timber/Hardwood
 - Any exterior surfaces

Please consult with your Skudo representative to determine which Skudo product is best for your project.