

Last Revision: 2/1/2022



Carpet Cover
Carpet Protection Film
Safety Data Sheet (SDS)

Last Revision: February 1, 2022

SECTION 1: IDENTIFICATION

Product Identifier	Carpet Protect, Self-adhesive film
Company Identification	Skudo LLC 11120 Zodiac Ln Dallas, TX 75229 USA Ph: (972) 993-0777 Fx: (972) 993-0700
Emergency Number	Dial 911
Recommended Use	Carpet Protection

SECTION 2: HAZARD IDENTIFICATION

Eye Contact	Eye Contact not expected during normal use
Skin Contact	No health effects anticipated
Inhalation	No health effects anticipated
If Swallowed	Ingestion not expected during normal use

SECTION 3: COMPOSITION

Chemical Name	Polyolefin
Common Name	Acrylic Copolymer Formulation
CAS Number	N/A
Impurities and Stabilizing Additives	N/A

SECTION 4: FIRST-AID MEASURES

Last Revision: 2/1/2022

Eye Contact	Immediately flush eyes with large amounts of water. Seek immediate medical attention. Irritation, redness, scratching of cornea may occur.
Skin Contact	No first-aid anticipated
Inhalation	No first-aid anticipated
If Swallowed	No first-aid anticipated
In Case of Emergency	Dial 911

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Methods	Carbon Dioxide or Water Spray
Special Procedures	Full protective equipment and self-contained breathing apparatus
Unusual Fire Hazards	Dense smoke may be emitted

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions	N/A
Emergency Procedures	N/A
Containment Methods	N/A
Cleanup Procedures	N/A

SECTION 7: HANDLING AND STORAGE

Safe Handling Precautions	Max. 6 month application
Handling Incompatible Chemicals	Water, Oils, other contaminants and direct UV light
Minimizing Environmental Release	N/A
Temperature Range	45 Degrees - 90 Degrees °F / 7 - 33°C
Recommended Safe Storage	Store in a cool, dry place

SECTION 8: EXPOSURE CONTROLS

Eye Protection	Avoid eye contact
Skin Protection	N/A
Recommended Ventilation	N/A
Respiratory Protection	N/A
Prevention of Accidental Ingestion	N/A
Fire and Explosion Avoidance	Avoid high heat/ flames

Last Revision: 2/1/2022

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Plastic Film
Flammability	N/A
Adhesive Base	Water
Vapor Pressure	N/A
pH	N/A
Relative Density	N/A
Melting Point / Freezing Point	150 to 400 Degrees F / 65 - 200°C
Specific Gravity	<1,000
Solubility	0.0%
Flash Point	345 Degrees C / 650 F
Evaporation Rate	N/A
Partition Coefficient	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A
Viscosity	N/A

SECTION 10: STABILITY AND REACTIVITY

Reactivity	N/A
Chemical Stability	Stable
Other	Avoid high heat/ flames

SECTION 16: OTHER INFORMATION

SOS Prepared	June 2015
Latest Revision	February 2022

Disclaimer: Skudo LLC makes no representation as to the completeness and accuracy of the data contained in this data sheet. It is the user's obligation to evaluate and use this product safely and to comply with all relevant Federal, State and Local Government laws and regulations. Skudo LLC shall not be responsible for loss, damage or injury resulting from reliance upon or failure to adhere to any recommendations or information contained herein, from abnormal use of the material, or any hazard inherent in the nature of the material. 5102.70