

# Safety Data Sheet

**Product: SkudoBoard** 

Issue Date: February 1, 2022

# 1. IDENTIFICATION

1.1 Product Name: SkudoBoard

1.2 Chemical Classification Flame Retardant PP Board

1.3 Product Operation Suggestions Construction

and Restrictions:

1.4 Company Introduction

Manufacturer/Supplier Name: Skudo LLC

Address: 11120 Zodiac Ln

Dallas, TX 75229

USA

Tel: +1 (972) 993-0777

Fax: +1 (972) 993-0700

E-mail <u>info@skudousa.com</u>

Emergency Tel: +1 (972) 993-0777

1.5 First Issue Date June 18, 2018

# 2. HAZARDS IDENTIFICATION

2.1 Color: Grey

Physical State: Board or Panel.

Odor: Inodorous or slight odor.

2.2 Hazard Classification: No harm.

2.3 Signs and Precautionary Statements

Graphic Symbol: None.
Signal Word: None.

2.4 Cardinal Symptom after Contact

Eye Protection: Use safety glasses. Safety glasses should be

consistent with Directive 89/686/EEC Category 2. If there is a potential for exposure to board which could cause eye discomfort, wear chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent. If exposure causes eye

discomfort, use a full-face respirator.

Skin Protection: No precautions other than clean body-covering

clothing should be needed.

Hand Protection: Chemical protective gloves should not be

needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized. Use gloves with insulation for thermal protection, when needed.

Respiratory Protection: Use an approved air-purifying respirator when

vapors are generated at increased temperatures or when dust or mist is present. Use the following CE approved air-purifying respirator: When dust/mist are present use a Particulate filter, type P2. When combinations of vapors, acids, or dusts/mists are present use an organic vapor cartridge with a particulate pre-filter, type AP2.

Ingestion: Low toxicity. It may cause choking if swallowed.

2.5 Emergency Measures: Avoid contact with eyes.

2.6 Other Hazards: Unknown

### 3. COMPOSITION INFORMATION ON INGREDIENTS

3.1 Chemical Classification: Compound Mixture

3.2 Risk Composition: Flame Retardant PP Board

<u>Chemical Name</u>	CAS#	<u>% (w/w)</u>
Polypropylene	9003-07-0	55%-80%
Flame Retardant		1%-10%
Filler and assistant		1%-25%

#### 4. FIRST AID MEASURES

First Aid Measures 4.1

> Eye Contact: Flush eye thoroughly with water for several

> > minutes. Remove contact lenses after the initial 1-

2 minutes and continue flushing for several additional minutes. If effects occur, consult a doctor, preferably an ophthalmologist.

Skin Contact: If molten material meets skin, do not apply ice

> but cool under ice water or running stream of water. Do not attempt to remove the material from the skin. Removal may result in severe tissue damage. Seek medical attention immediately.

Inhalation: Move person to fresh air; if effects occur, consult

a doctor.

Ingestion: If swallowed, seek medical treatment. May cause

> gastrointestinal blockage. Do not induce vomiting unless directed to do so by medical personnel.

4.2 Notes to Doctor: If burn is present, treat as any thermal burn, after

decontamination. No specific antidote.

Treatment of exposure should be directed at the control of symptoms and the clinical condition of

the patient.

#### 5. FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media: Water fog or fine spray. Dry powder fire

extinguishers, carbon dioxide fire extinguishers,

foam.

5.2 Prohibited Fire Extinguishing Agent: Unknown.

5.3 Special Drainage: None.

Special Fire Extinguishing Procedure: Evacuate personnel from fire. Isolate of fire and 5.4

prohibit unwanted people into fire zone. Soak the burning material thoroughly with water to cool and prevent reignition. If the material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to cool fire zone. Extinguish small fire with hand-held dry power fire extinguisher or carbon dioxide

extinguisher.

Ingestion: If swallowed, seek medical treatment. May cause

gastrointestinal blockage. Do not induce vomiting unless directed to do so by medical personnel.

5.5 Special Protective Equipment for

Firefighters:

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective clothing (includes fire helmet, coat, trousers, boots and gloves). If protective equipment is not available or not used, fight fire from a protected location or

safe distance.

#### 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions: Spilled material may cause a slipping hazard. Use

appropriate safety equipment.

6.2 Environmental Precautions: Prevent from entering soil, ditches, sewers,

waterways and / or groundwater.

6.3 Elimination Method: Contain spilled material if possible. Sweep up.

Collect in suitable and properly labeled

container.

# 7. HANDLING AND STORAGE

7.1 Handling Precautions: Workers should be protected from the possibility

of contact with molten resin. Do not get molten material in eyes, on skin or clothing. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions,

electrically bond and ground equipment and do not permit dust to accumulate. Dust can be

ignited by static.

7.2 Storage Precautions: Store in accordance with good manufacturing

practices.

7.3 Unsuitable Packing Materials: Unknown.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Industrial Hygiene Standards

Exposure Limit: Unknown

8.2 Engineering Controls Good general ventilation should be sufficient for

Ventilation most conditions.

Local exhaust ventilation may be necessary for

some operations.

8.3 Personal Protection

Respiratory Protection: Use an approved air-purifying respirator when

vapors are generated at increased temperatures or when dust/mist is present. The following should be effective types of air-purifying respirators: When dust/mist are present use a filter. When combinations of vapors, acids, or dusts/mists are present use an organic vapor cartridge with a

particulate pre-filter.

Eye Protection: Use safety glasses. If there is a potential for

exposure to particles which could cause eye discomfort, wear chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Hand Protection: Use gloves to protect from chemical injury.

Selection of gloves will depend on the task. Use

gloves with insulation for thermal.

Skin and Body Protection: No precautions other than clean body-covering

clothing should be needed.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical State: Board or Panel

9.2 Color: Grey

9.3 Odor: Inordorous or slight odor

9.4 pH Not applicable

9.5 Melting Point: 329-329°F (165-200°C).

9.6 Boiling Point: Not applicable

9.7 Flash Point: Not tested

9.8 Blast Limit in Air

Upper Not tested.
Lower: Not tested.

9.9 Vapor Density (25°C): Not applicable.

9.10 Vapor Pressure air=1): Not applicable.

9.11 Density: 0.9-1.1g/cm<sup>3</sup>

9.12 Solubility: Negligible.

9.13 Distribution Coefficient (N-oc- Not tested.

tanol/Water):

9.14 Autoignition Temperature: Not tested.
9.15 Decompose Temperature: Not tested.
9.16 Odor Threshold: Not tested.

9.17 Evaporation Rate: Not applicable.9.18 Flammability (Solid, Gas): Not applicable.

10. STABILITY AND REACTIVITY

10.1 Stability: Stable.

10.2 Conditions to Avoid: Products can decompose at elevated

temperature.

10.3 Incompatible Materials: Unknown.

10.4 Hazardous Polymerization: Will not occur.

10.5 Hazardous Decomposition: Decomposition products depend upon

temperature, air supply and the presence of other materials. Processing may cause the

releases of irritant smoke and other

decomposition. When temperature exceeds the melting point, this product may release polymer fragments. Decomposition products could include and are not limited to: aldehydes,

alcohols, organic acids and some other marginal

hydrocarbons.

11. TOXICOLOGICAL INFORMATION

11.1 Exposure Ways: Inhalation, skin contact and accidental

ingestion.

11.2 Effects of Over Contact: No notable harms under normal handling.

11.3 Acute Toxicity:

Eye Contact: Direct contact may cause eye irritation

experienced as mild discomfort and redness.

Skin Absorption: Estimated LD50, rabbit > 2000 mg/kg. No serious

effects for transitory contact.

Ingestion: Estimated LD50, rat > 5000 mg/kg. Very low

ingestion hazards under normal handling.

Inhalation: Estimated LC50, rat > 50 mg/1(4h, dusts/mist). No

serious effects for transitory contact.

11.4 Chronic Toxicity

Skin: Repeated or long-time contact may cause skin

irritation and dermatitis.

Ingestion: Repeated or massive ingestion may cause

physical harm.

Inhalation: Not applicable.

11.5 Repeated Dose Toxicity: Additives are encapsulated in the product and

are not expected to be released under normal

processing conditions or foreseeable

emergency.

11.6 Chronic Toxicity and Carcinogenicity: Not applicable.
11.7 Growth Toxicity: Not applicable.
11.8 Procreation Toxicity: Not applicable.

11.9 Inheritance Toxicity: Not applicable.

### 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity: Not expected to be acutely toxic, but may

cause adverse effects by physical/mechanical

means.

12.2 Resistance and Degradability: This water-insoluble polymeric solid is expected

to be insert in the environment.

12.3 Migration in Soil: It will remain in the soil in the terrestrial

environment. And it will sink into the aquatic

environment.

#### 13. DISPOSAL CONSIDERATIONS

13.1 Product Waste Disposal Ways: Disposal according to local regulatory.

13.2 Packing Waste Disposal Ways: Disposal according to local regulatory.

# 14. TRANSPORT INFORMATION

14.1 Road and Rail Transport: Not regulated.

14.2 Sea Transportation (IMDG): Not regulated by IMDG codes.

14.3 Air Transportation (IATA): Not regulated by IATA.

14.4 Specific Operational Requirements: None.

#### 15. REGULATORY INFORMATION

15.1 Applicable Regulations: Regulations for the Safe Use of Chemicals in

Workplace [(1996) 423#, sent by Department of

Labor]

Public Summons for General Rules of Chemicals

Classification and Hazard [GB 13690-2009]

15.2 Chemical Storage

TSCA: All components of this product are on the TSCA

Inventory or are exempt from TSCA Inventory

requirements.

AICS:

All substances contained in this product are

listed or are exempt from requirements.

DSL: All substances contained in this product are

listed on DSL Inventory or are exempt from DSL

Inventory requirements.

IECSC: All substances contained in this product are

listed or are exempt from requirements.

EINECS: All substances contained in this product are

listed or are exempt from requirements.

KECL: All substances contained in this product are

listed or are exempt from requirements.

PICCS: All substances contained in this product are

listed or are exempt from requirements.

HSNO: All substances contained in this product are

listed or are exempt from requirements.

ENCS/ISHL: All substances contained in this product are

listed or are exempt from requirements.

# 16. OTHER INFORMATION

The product safety instructions in this safety data sheet are according to our existing knowledge and experience. This sheet does not describe the product components and specifications. Any public and/or for specific purpose product characteristics should not be removed from this data sheet. All users have responsibility and obligation to ensure the intellectual property rights of products and to abide the relevant laws and regulations.