

STAIR GUARD/ CORNER GUARD





Description

SkudoBoard STAIR GUARD/CORNER GUARD is a heavy duty, synthetic, rigid board that is specifically designed to fit perfectly around sharp edges, such as corners, stair treads, and wall edges. SkudoBoard STAIR GUARD/CORNER GUARD is lightweight, easy to install, and extremely impact resistant. The extra layer of protection from the fabric backed underside guards from dents, cracks, scuff marks, and scratches on stairs and edges due to carts, equipment, and general construction traffic.

The textured surface of SkudoBoard STAIR GUARD/CORNER GUARD provides high slip resistance in addition to being fire retardant and water resistant. The STAIR GUARD version also features a safety orange grip tape on the tread for additional slip-resistance.

SkudoBoard STAIR GUARD/CORNER GUARD is also resistant to curling and warping - reducing safety hazards on your jobsite. STAIR GUARD/CORNER GUARD has the same compression strength as SkudoBoard delivering protection from dropping objects, keeping your surfaces safe. It is also reusable – saving you time, hassle, and money.

Features & Benefits

- Fits perfectly around corners, stair treads, and wall edges
- Water resistant, can be used on exterior surfaces
- Fabric backed underside for an added layer of protection
- Replaces curling Masonite and plywood
- Fire Retardant (ASTM E 648 Class 1, 16 CFR 1630)
- Test-proven slip resistance in wet conditions (ANSI/NFSI B101.3-2012)
- Extremely high impact resistance spreads impact loads
- Ideal for protection from carts, lifts, dropped tools and materials
- Well suited for protecting surfaces from jobsite traffic and debris
- Light weight, easy to handle and reusable
- Far superior to cardboard protection products



Extremely high impact resistance



Slip-resistant for safety



Protects edges and stairs







Product Data

SkudoBoard STAIR GUARD

• Dimensions: 48" x 11.5" x 6.5"

• Product SKU #BOARD-STAIR-48x11.5x6.5

Weight: 1.5 lbs/pcThickness: 5mm (1/4")Color: Light Cray

Color: Light Gray

Includes safety orange grip tape

SkudoBoard CORNER GUARD

• Dimensions: 48" x 6" x 6"

Product SKU #BOARD-CORNER-FR-48x6-AO

Weight: 1.25 lbs/pcThickness: 5mm (1/4")Color: Light Gray

5 mm, 1500 g/m²

Property	Test Standard	Units	Result Average Value	Standard Deviation
Board Thickness		mm	5.00	0.10
Unit Weight		g/m²	1524	66
Flexural Strength, MD	ASTM D790 (Modified)	psi	1433	87
Flexural Strength, TD	ASTM D790 (Modified)	psi	1344	78
Flexural Modulus, MD	ASTM D790 (Modified)	Kpsi	120	9
Flexural Modulus, TD	ASTM D790 (Modified)	Kpsi	112	5
Gardner Impact Mean-Failure Impact	ASTM D5420	in	4.3	0.9
Flat Crush Resistance	ISO 3035 TAPPI-825	psi	> 1000	
Edge Crush Resistance	ISO 3037 TAPPI-811	lb./in	88	22

Note:

- 1. Flexural Test: 12" x 12" sample with 10" span, 3-point bending
- 2. Gardner Impact Test: 8 lb. steel-rod impact mass
- 3. MD: Machine Direction
- 4. TD: Transverse Direction
- 5. Kpsi = 10^3 psi