





Application



IMPORTANT: Before installing any surface protection system, make sure that the surface to be protected is dust and debris free.



HOW TO APPLY: SkudoBoard 4X8

Installing SkudoBoard is a simple and quick process. Like any other floor covering installation, it is best practice to take some time before installation to figure out the most efficient layout, minimizing small cut infills.



SkudoBoard 4x8 can be installed stack bond or running bond (offset). Skudo recommends leaving an expansion gap of 1/16th "as boards can expand in extremely hot conditions.

Tape the seams using a minimum 3" wide trafficable tape suitable for external and internal use; for larger projects, Skudo recommends a walk-behind tape dispenser be used.

HOW TO APPLY: SkudoBoard Interlock

Prepare the surface as above. SkudoBoard interlock is locked into place by pressing down the interlocking tabs, which will stay in place without tape when exposed to foot and small cart traffic. Taping the tabs will offer better stability where heavier traffic is expected.



Innovative, purpose-built surface protection systems. This is all we do. www.skudousa.com 1-888-SKUDO-11 (1-888-758-3611)







Important Tips & Maintenance



Clean the area of dirt, dust, and debris before applying to ANY surface.



Use a high-quality tape (at least 3" wide) to tape the seams. Skudo recommends using T-Rex Tape or Gorilla Tape. (Contact Skudo to purchase directly.)



For larger projects, Skudo recommends using the Skudo Walk-Behind Tape Dispenser for easy application.



SkudoBoard is NOT breathable.



Hydration lines are possible if using on fresh concrete. Please check with your Skudo representative if this is a concern.



SkudoBoard is suitable for both horizontal and vertical surfaces.

Additional SkudoBoard protection available:





V1.0 11.13.23

Innovative, purpose-built surface protection systems. This is all we do. www.skudousa.com 1-888-SKUDO-11 (1-888-758-3611)