Skudo® TACK-MAT® HT

Learn More!

Skudo®

Description

Skudo's Heavy Traffic (HT) Tack-Mat provides durable, temporary surface protection for horizontal interior surfaces, including floors and stairs. Designed to withstand machinery, heavy construction traffic, and demanding jobsite conditions, HT Tack-Mat offers reliable protection for commercial, residential, and healthcare environments.

Featuring a unique self-stick surface, installation is quick and easy – simply peel away the release paper and apply. Fire/flame retardant and treated with antibacterial/antimicrobial properties, HT Tack-Mat helps maintain cleaner, safer environments while protecting underlying surfaces for up to 12 months.



Slip Resistant Surface



Perfect for stairs



Antibacterial, Antimicrobial



Extremely Durable

Benefits

- Strong bond with the surface blocks any dirt and debris from staining or damaging the protected substrate
- Provides protection from machinery, carts and foot traffic
- Protects from small spills of many chemicals, solvents, paints, and oils.
- Slip resistant surface that is seamless and stationary
- Protects against color changing UV rays
- Can be used in any temperature : -20°F to +200°F
- Proven Fire/Flame retardant according to Class 1 ASTM E 648 and NFPA 253 standards.
- Antibacterial/Antifungal: Test-verified protection against bacteria and molds that cause infection. (ISO-20743)
- Easy to adjust or inspect surface, simply peel up and re-position

Uses

Protects all surfaces during construction/remodeling including:

- Marble, Granite, and Stone *
- Hardwood* and laminate
- Ceramic and Porcelain Tile
- Glass, Epoxies, and Metals
- Sheet Vinyl
- Showers, bathtubs, and countertops

*Please see "Limitations" section (pg 2)

Peel & Stick

Innovative, purpose-built surface protection systems. This is all we do.

www.skudousa.com 1-888-SKUDO-11 (1-888-758-3611)

Skudo® TACK-MAT® HT

Skudo®

Application & Removal

All Skudo Tack-Mat products are easily applied by peeling off the release paper and pressing down onto the surface. Apply seam tape to the overlap joints to firmly secure. Simply peel up Tack-Mat leaving a clean, undamaged surface.



Easy Application

For detailed step-by-step Tack-Mat application directions and video, please visit our website: **https://www.skudousa.com/products/tack-mat/#how-to-apply**

Heavy Traffic (HT) Tack-Mat Product Data

- Width : 40”
- Length : 165’
- Surface Area : 550 SF
- Mat Thickness : 1/16”
- Roll Weight : 81 lbs
- Color : Orange
- Product SKU : TM-HT-3.3-165



Limitations

- **INTERIOR USE ONLY.** Skudo HT Tack-Mat is intended for **interior use only** and is not suited for areas that will be exposed to inclement weather and wind. If exposure to the elements is a concern, Skudo recommends the Heavy Traffic (HT) Commercial Mat System. Please consult with your Skudo representative for more details.
- **All adhesives have the potential to lift finished coatings or paint depending on the condition and age of the surface.** Testing a small piece in a non-critical area will help you judge suitability for use.
- If applying to hardwood flooring, only use Skudo Tack-Mat on sealed hardwood with a hard wearing factory finished surface (eg : Aluminum Oxide). If in question, please contact Skudo for suitability testing.

- **Skudo Tack-Mat should NOT be applied to:**
  - Concrete
  - Limestone
  - Rough/Textured Surfaces
  - Non-factory finished Hardwood
  - Raw or unfinished Timber/Hardwood
  - Any exterior surfaces

Please consult with your Skudo representative to determine which Skudo product is best for your project.

Innovative, purpose-built surface protection systems. This is all we do.