SKUDO BOARD

Learn More!

Skudo

Description

SkudoBoard is a heavy-duty, rigid synthetic board designed to provide superior surface protection under forklifts and general construction traffic. An effective alternative to Masonite or plywood, it's ideal for protecting floors beneath workstations used for pipe cutting, finish carpentry, painting, and other construction activities.

The textured surface is fire retardant and water resistant, while resisting curling and warping to help reduce jobsite safety hazards. High compression strength helps protect surfaces from dropped objects and distributes loads under forklifts to safeguard floors. SkudoBoard can also be used for demanding vertical protection applications.

For added surface protection, SkudoBoard is available in a **Fabric Back** version featuring a unique fabric underside designed for use on sensitive surfaces such as tile, stone, marble, vinyl, and hardwood, helping prevent scratches, chips, and other damage.

For best results, Skudo recommends using Skudo Premium Seam Tape to securely join boards during installation.

Features & Benefits

- Water resistant for use on interior and exterior surfaces
- Reusable, easy to clean and take to the next project
- Fire retardant (ASTM E648 Class 1; 16 CFR 1630)
- Tested slip resistance in wet conditions (ANSI/NFSI B101.3-2012)
- High impact resistance helps distribute loads and protect underlying surfaces
- Ideal for workstations involving pipe cutting, finish carpentry, painting, and other construction activities
- Provides reliable protection under forklifts and material carts
- Protects floors from heavy workstation traffic, tools, and debris
- Lightweight, easy to handle, and reusable
- Resists curling and warping common with Masonite and plywood
- More durable and reliable than cardboard protection products
- Available in a Fabric Back version for added protection against scratches, chips, and surface damage



High-Impact protection



Water resistant, resists curling and warping



Use under ladders, carts, and workstations



Fabric Back version available for additional protection

Innovative, purpose-built surface protection systems. This is all we do.

www.skudousa.com 1-888-SKUDO-11 (1-888-758-3611)

Learn More!

SkudoBoard Product Data

SkudoBoard (Standard)
- Dimensions: 4'W x 8'L
- Square Footage: 32 sq. ft./board
- Weight: 10 lbs/sheet
- Thickness: 5mm (1/4")
- Color: Grey
- SKU#: BOARD-FR-STD-4x8-GREY-A



SkudoBoard - *Fabric Back*
- Dimensions: 4'W x 8'L
- Square Footage: 32 sq. ft./board
- Weight: 10 lbs./sheet
- Thickness: 5mm (1/4")
- Color: Grey
- SKU#: BOARD-FR-FAB-4x8-GREY-A



SkudoBoard Premium Seam Tape
16 mil heavy-duty tape, recommended for joining boards
- Length: 36 yards long
- Thickness: 16 mil
- Color: Black
- SKU#: BOARD-TAPE-SKUDO-36-BLK



Walk-Behind Tape Dispenser
Back-saving walk-behind tape dispenser, recommended for installing SkudoBoard 4' x 8' sheets.
- Weight: 10 lbs.
- Color: Orange
- SKU#: AC-TAPE-APPLICATOR



Application

Clean the area of dirt, dust, and debris before applying to ANY surface.

SkudoBoard 4' x 8' can be installed in a stack-bond or running-bond (offset) pattern. Leave a 1/16" expansion gap between boards to accomodate expansion in extremely hot conditions.

Tape all seams using a minimum 3" wide trafficable tape suitable for external and internal use. For best results, Skudo recommends using our Skudo Premium Seam Tape and Walk Behind Tape Dispenser.

*Visit our website (**www.SkudoUSA.com**) for more best practices and additional SkudoBoard protection solutions, including Column Guard, Stair Guard, Corner Guard, ResiBoard, and BEASTBoard.*



Stack-Bond Installation



Running-Bond Installation

Innovative, purpose-built surface protection systems. This is all we do.

www.skudousa.com 1-888-SKUDO-11 (1-888-758-3611)